

Alfa Laval DOC60

Brazed plate heat exchanger for oil cooling

Alfa Laval DOC - Dedicated oil coolers are brazed plate heat exchangers with robust connection flanges, which are suitable for hydraulic oil cooling applications.

Applications

Oil cooling

Benefits

- Compact
- Easy to install
- Self-cleaning
- · Low level of service and maintenance is required
- All units are pressure and leak tested
- Gasket free
- Very robust connection flanges
- Integrated mounting bracket

Design

The brazing material seals and holds the plates together at the contact points ensuring optimal heat transfer efficiency and pressure resistance. Using advanced design technologies and extensive verification guarantees the highest performance and longest possible service life.

The robust connection flanges with internal threads and integrated mounting brackets are specifically designed for oil cooling under tough operating conditions and reduces costs because of easy installation. Additionally, the flanges allow significantly higher torque at installation than conventional connections.



Technical Data

Standard materials

otandara matonalo		
Cover plates	Stainless steel	
Connections	Stainless steel	
Plates	Stainless steel	
Brazing filler	Copper	

Dimensions and weight¹

A measure (mm)	13 + (2.32 * n)
A measure (inches)	0.51 + (0.09 * n)
Weight (kg) ²	2.1 + (0.18 * n)
Weight (lb) ²	4.63 + (0.4 * n)

- 1. n = number of plates
- 2. Excluding connections


Standard data

Volume per channel, litres (gal)	0.10 (0.027)	
Max. particle size, mm (inch)	1 (0.039)	
Max. flowrate ¹ m ³ /h (gpm)	8.8 (38.7)	
Flow direction	Parallel	
Min. number of plates	10	
Max. number of plates	120	

1. Water at 5 m/s (16.4 ft/s) (connection velocity)


Dimensional drawing


Measurements in mm (inches)




Design pressure and temperature

DOC60 - PED approval pressure/temperature graph







Designed for full vacuum.

Alfa Laval plate heat exchangers are available with a wide range of pressure vessel approvals. Please contact your Alfa Laval representative for more information.

NOTE: Values above are to be used as an indication. For exact values, please use the drawing generated by the Alfa Laval configurator or contact your local Alfa Laval representative.

CHE00039EN 2016-12

Alfa Laval reserves the right to change specifications without prior notification.



