

Alfa Laval T21

Gasketed plate heat exchanger for a wide range of applications

Introduction

Alfa Laval Industrial line is a wide product range that is used in virtually all types of industry.

Suitable for a wide range of applications, this model is available with a large selection of plate and gasket types.

Applications

- Biotech and Pharmaceutical
- Chemicals
- Energy and Utilities
- Food, Dairy and Beverages
- Home and Personal care
- HVAC and Refrigeration
- Machinery and Manufacturing
- Marine and Transportation
- Mining, Minerals and Pigments
- Pulp and Paper
- Semiconductor and Electronics
- Steel
- Water and Waste treatment

Benefits

- High energy efficiency low operating cost
- Flexible configuration heat transfer area can be modified
- Easy to install compact design
- High serviceability easy to open for inspection and cleaning and easy to clean by CIP
- Access to Alfa Laval's global service network

Features

Every detail is carefully designed to ensure optimal performance, maximum uptime and easy maintenance. Selection of available features, depending on configuration some features may not be applicable:

- Five-point alignment
- T-bar roller
- CurveFlowTM distribution area
- Glued gasket
- ClipGrip[™] gasket attachment
- Offset gasket groove
- OmegaPortTM noncircular port holes
- Leak chamber



- Elongated nut
- FlexFlowTM plate design
- Compact frame
- · Bearing boxes
- Fixed bolt head
- Key hole bolt opening
- Lifting lug
- Lining
- Lock washer
- Tightening bolt cover


Alfa Laval 360° Service Portfolio

Our extensive service offering ensure top performance from your Alfa Laval equipment throughout its life cycle. The Alfa Laval 360 Service Portfolio include installation services, cleaning and repair as well as spare parts, technical documentation and trouble shooting. We also offer replacement, retrofit, integrity testing, monitoring and much more.

For information about our complete service offering and how to contact us - please visit www.alfalaval.com/service.

Dimensional drawing

Measurements mm (inches)



	Frame type	Н	W	h
	FM ALS, PED,	0000 F (01 0")	755 (29.7")	280 (11.0")
	Marine ¹	2082.5 (81.9")		
	FG ALS, PED, ASME	2135 (84.0")	780 (30.7")	285 (11.2")
	FD ALS, PED, ASME	2173 (85.5")	780 (30.7")	323 (12.7")
	FS ASME	2173 (85.5")	780 (30.7")	323 (12.7")
	FT ALS, PED, ASME	2173 (85.5")	780 (30.7")	323 (12.7")

¹ Marine includes the pressure vessel codes: ABS, BV, CCS, ClassNK, DNV, KR, LR, RINA, and RMRS.

Technical data

Plates	Туре	Free channel, mm (inches)	
М	Single plate	3.97 (0.15)	
Ρ	Single plate	2.8 (0.11)	
В	Single plate	1.92 (0.075)	
Materials			
Heat transfer plates		304, 316, 254, C276, D205, C2000, Alloy 33, G30, Ni, Ti, TiPd	
Field gaskets		NBR, EPDM, FKM, HNBR, HeatSeal	
Flange connections		Metal lined: stainless steel, 254, C276, D205, C2000, G30, Ni, Ti, TiPd Rubber lined: NBR	
Frame and pressure plate Carbon steel, epoxy painted		e Carbon steel, epoxy painted	

Other materials may be available on request.

Operational data

Frame type	Max. design pressure barg (psig)	Max. design temperature °C (°F)
FM, PED	10.4 (151)	200 (392)
FM, pvcALS	10.4 (151)	200 (392)
FM, Marine ¹	10.4 (151)	100 (212)
FG, pvcALS	16.0 (232)	200 (392)
FG, ASME	10.4 (151)	250 (482)
FG, PED	16.0 (232)	200 (392)
FD, pvcALS	25.0 (362)	200 (392)
FD, ASME	21.0 (304)	250 (482)
FD, PED	25.0 (362)	200 (392)
FS, ASME	36.0 (522)	250 (482)
FT, PED	40.0 (580)	200 (392)
FT, ALS	40.0 (580)	200 (392)
FT, ASME	41.4 (600)	250 (482)

¹ Marine includes the standards: ABS, BV, CCS, ClassNK, DNV, KR, LR, RINA, and RMRS.

Extended pressure and temperature rating may be available on request.

General remarks for technical information

- The global offering presented in this leaflet may not be available for all regions
- All combinations may not be configurable

Flange connections

Frame type	Connection standard
	EN 1092-1 DN200 PN10
FM, pvcALS	ASME B16.5 Class 150 NPS 8
	JIS B2220 10K 200A
	EN 1092-1 DN200 PN10
M, PED	ASME B16.5 Class 150 NPS 8
FM, Marine ¹	EN 1092-1 DN200 PN10
	ASME B16.5 Class 150 NPS 8
	JIS B2220 10K 200A
	EN 1092-1 DN200 PN16
	EN 1092-1 DN200 PN25
FG, pvcALS	ASME B16.5 Class 150 NPS 8
	JIS B2220 10K 200A
	JIS B2220 16K 200A
	ASME B16.5 Class 150 NPS 8
FG, ASME	EN 1092-1 PN16
	EN 1092-1 DN200 PN10
FG, PED	EN 1092-1 DN200 PN16
FG, FED	EN 1092-1 DN200 PN25
	ASME B16.5 Class 150 NPS 8
=D, pvcALS	EN 1092-1 DN200 PN25
	ASME B16.5 Class 300 NPS 8
	JIS B2220 20K 200A
	ASME B16.5 Class 150 NPS 8
FD, ASME	EN1092–1 PN25
	ASME B16.5 Class 300 NPS 8
	EN 1092-1 DN200 PN25
FD, PED	ASME B16.5 Class 300 NPS 8
FS, ASME	ASME B16.5 Class 300 NPS 8
	EN 1092-1 DN200 PN40
FT, ALS	ASME B16.5 Class 300 NPS 8
TI, ALO	ASME B16.5 Class 400 NPS 8
	JIS B2220 200A 30K
	EN 1092-1 DN200 PN40
FT, PED	ASME B16.5 Class 300 NPS 8
	ASME B16.5 Class 400 NPS 8
	ASME B16.5 Class 300 NPS 8
T, ASME	ASME B16.5 Class 400 NPS 8
	EN 1092-1 DN200 PN40

¹ Marine includes the standards: ABS, BV, CCS, DNV, ClassNK, KR, LR, RINA, and RMRS.

Standard EN1092-1 corresponds to GOST 12815-80 and GB/T9124.1.

This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval AB (publ) or any of its affiliates (jointly "Alfa Laval"). No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

200004046-14-EN-GB

How to contact Alfa Laval Up-to-date Alfa Laval contact details for all countries are always available on our website at www.alfalaval.com



QDIL I COPAC

inf⊚ ►/CESEHSA.com.mx

