

Alfa Laval T8

Gasketed plate heat exchanger for a wide range of applications

Introduction

Alfa Laval Industrial line is a wide product range that is used in virtually all types of industry.

Suitable for a wide range of applications, this model is available with a large selection of plate and gasket types.

Applications

- Biotech and Pharmaceutical
- Chemicals
- Energy and Utilities
- Food, Dairy and Beverages
- HVAC and Refrigeration
- · Machinery and Manufacturing
- Marine and Transportation
- Mining, Minerals and Pigments
- Pulp and Paper
- Semiconductor and Electronics
- Steel

Benefits

- High energy efficiency low operating cost
- Flexible configuration heat transfer area can be modified
- Easy to install compact design
- High serviceability easy to open for inspection and cleaning and easy to clean by CIP
- Access to Alfa Laval's global service network

Features

Every detail is carefully designed to ensure optimal performance, maximum uptime and easy maintenance. Selection of available features, depending on configuration some features may not be applicable:



- Corner guided alignment system
- CurveFlowTM distribution area
- ClipGripTM gasket attachment
- Offset gasket groove
- OmegaPortTM noncircular port holes
- Leak chamber
- Fixed bolt head
- Key hole bolt opening
- Lifting lug
- Lining



- Lock washer
- Tightening bolt cover


Alfa Laval 360° Service Portfolio

Our extensive service offering ensure top performance from your Alfa Laval equipment throughout its life cycle. The Alfa Laval 360 Service Portfolio include installation services, cleaning and repair as well as spare parts, technical documentation and trouble shooting. We also offer replacement, retrofit, integrity testing, monitoring and much more.

For information about our complete service offering and how to contact us - please visit www.alfalaval.com/service.

Dimensional drawing

Measurements mm (inches)



Frame type	Н	W	h
FM	890 (35.04")	400 (15.78")	142 (5,59")
FG	890 (35.04")	400 (15.78")	142 (5,59")
FG, ASME	890 (35.04")	416 (16.38")	142 (5,59")

The number of tightening bolts may vary depending on pressure rating.

Technical data

Plates	Type	Free channel, mm (inches)	
В	Single plate	2.3 (0.091)	
М	Single plate	3.9 (0.15)	

Materials	
Heat transfer plates	304/304L, 316/316L
Heat transfer plates	Ti
Field gaskets	NBR, EPDM
Flance connections	Metal lined: stainless steel, titanium
Flange connections	Rubber lined: NBR
Frame and pressure plate	Carbon steel, epoxy painted

Other materials may be available on request.

Operational data

Frame type	Max. design pressure barg (psig)	Max. design temperature °C (°F)
FM, PED	13.0 (188)	180 (356)
FM, pvcALS	13.5 (196)	180 (356)
FG, pvcALS	15.5 (225)	180 (356)
FG, ASME	10.3 (150)	250 (482)
FG, PED	17.5 (253)	180 (356)

Extended pressure and temperature rating may be available on request.

General remarks for technical information

- The global offering presented in this leaflet may not be available for all regions
- All combinations may not be configurable

Flange connections

Frame type	Connection standard
FM, pvcALS	EN 1092-1 DN80 PN10
	ASME B16.5 Class 150 NPS 3
	JIS B2220 10K 80A
EM DED	EN 1092-1 DN80 PN10
FM, PED	ASME B16.5 Class 150 NPS 3
	EN 1092-1 DN80 PN16
EC DVALC	ASME B16.5 Class 150 NPS 3
FG, pvcALS	JIS B2220 10K 80A
	JIS B2220 16K 80A
FG. ASME	ASME B16.5 Class 150 NPS 3
FG, ASIVIE	EN 1092-1 DN80 PN16
FG, PED	EN 1092-1 DN80 PN16
ra, red	ASME B16.5 Class 150 NPS 3

Standard EN1092-1 corresponds to GOST 12815-80 and GB/T9124.1.

This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval AB (publ) or any of its affiliates (jointly "Alfa Laval"). No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

CHE 0077-5-EN-GB © Alfa Laval AB



inf@ D/CESEHSA.com.mx

