

Alfa Laval CB210 / CBH210 / CBK210

Brazed plate heat exchanger

Introduction

Alfa Laval CB brazed plate heat exchangers provide efficient heat transfer with a small footprint.

Applications

- HVAC heating and cooling
- Refrigeration
- Oil cooling
- Industrial heating and cooling

Benefits

- Compact
- Easy to install
- Self-cleaning
- Low level of service and maintenance is required
- All units are pressure and leak tested
- Gasket free

Branded Features



FlexFlow™

Superior thermal performance



PressureSecure

Unparalleled strength for demanding duties



ValuePlus

Total support – with value-adding options to fit your needs


Design

The brazing material seals and holds the plates together at the contact points ensuring optimal heat transfer efficiency and pressure resistance. Using advanced design technologies and extensive verification guarantees the highest performance and longest possible service life.

Different pressure ratings are available for different needs.

Asymmetric channels provide optimal efficiency in the most compact design.



Based on standard components and a modular concept, each unit is custom-built to meet the specific requirements of each individual installation.




Examples of connections



Compact flange



External thread



Welding

Technical data

Standard materials

Cover plates	Stainless steel
Connections	Stainless steel
Plates	Stainless steel
Brazing filler	Copper

Dimensions and weight

Dimensions and weight ¹

A-measurement (mm)	H, L, M: $11 + (2.18 * n)$ AH, AM: $11 + (2.14 * n)$
A-measurement (inches)	H, L, M: $0.43 + (0.09 * n)$ AH, AM: $0.43 + (0.08 * n)$
Weight (kg) ²	$12 + (0.61 * n)$
Weight (lb) ²	$26.46 + (1.34 * n)$

¹ n = number of plates

² Excluding connections


Standard data

	AH, AM (S1-S2): 0.636 (0.1680)
Volume per channel, litres (gal)	AH, AM (S3-S4): 0.416 (0.1099)
	H, L, M: 0.503 (0.1329)
Max. particle size, mm (inch)	1 (0.039)
Max. flowrate ¹ m ³ /h (gpm)	162 (713.3)
Flow direction	Parallel
	CB: 20
Min. number of plates	CBH: 20 CBK: 20
	CB: 360
Max. number of plates	CBH: 300 CBK: 204

¹ Water at 5 m/s (16.4 ft/s) (connection velocity)


Dimensional drawing

Measurements in mm (inches)




Design pressure and temperature


CB210/CBH210 – PED approval pressure/temperature graph



CBK210 – PED approval pressure/temperature graph



CB210/CBH210 – UL approval pressure/temperature graph



Designed for full vacuum.

Alfa Laval plate heat exchangers are available with a wide range of pressure vessel approvals. Please contact your Alfa Laval representative for more information.

NOTE: Values above are to be used as an indication. For exact values, please use the drawing generated by the Alfa Laval configurator or contact your local Alfa Laval representative.

Marine approvals

CBMK210 can be delivered with marine classification certificate (ABS, BV, CCS, ClassNK, DNV-GL, KR, LR, RINA)



inf @ /CESEHSA.com.mx

