



Arm Configuration



A	[1.63] 41,4	K	[0.50] 12,7
B	[4.81] 122,8	L	1/4 NPT
C	[2.72] 69,1	M	[2.31] 58,37
D	[0.25] 6,4	N	[1.50] 38,1
E	[2.21] 56,1	P	N/A
F	[0.25] 6,4	Q	N/A
G	[3.13] 79,5	R	[0.09] 2,3
H	[1.19] 30,2	MTG HOLES	[0.26] 6,6



NOTES :

1. INLET PRESSURE : [70 ~ 150 PSI] 4,8 ~ 10,3 bar
2. EXERTING FORCE : [850 ~ 1500 lbf] 3780 ~ 6670 N
3. CLAMPING RANGE : [0.09] 2,3
4. WEIGHT : [2.50 lb] 1,13 kg
5. REFER CATALOG PAGE FOR MORE DETAILS
6. DIMENSIONS AND TOLERANCES SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

COMPONENT	Pneumatic Toggle Clamps	
DIMENSIONS : [IN] MM	800	REV
TOLERANCES : ±[0.020] 0.51	800-SERIES	09/04/19
		SHEET
		1 of 1



15 Corporate Drive,
Auburn Hills, MI 48326, USA
Phone: 888-337-8226, Fax: 800-682-9689
www.destaco.com

This Drawing is the Property of DESTACO.
It contains confidential, proprietary information that is DESTACO property. Do not disclose to or duplicate for others except as authorized by DESTACO.