


**NOTES :**

1. MAX. HOLDING CAPACITY INNER : 1670 N [375 lbf]
2. MAX. HOLDING CAPACITY OUTER : 1220 N [275 lbf]
3. MAXIMUM EXERTING FORCE INNER @ [72 PSI] 5 bar : 2573 N [576 lbf]
4. MAXIMUM EXERTING FORCE OUTER @ [72 PSI] 5 bar : 1327 N [297 lbf]
5. WEIGHT : 0,75 kg [1.66 lbs]
6. BORE SIZE : 32 [1.26]
7. REFER CATALOG PAGE FOR MORE DETAILS
8. DIMENSIONS AND TOLERANCES SUBJECT TO CHANGE WITHOUT PRIOR NOTICE



**DESTACO**  
A STABILUS COMPANY

15 Corporate Drive,  
Auburn Hills, MI 48326, USA  
Phone: 888-337-8226, Fax: 800-682-9689  
www.destaco.com

This Drawing is the Property of DESTACO.  
It contains confidential, proprietary information that is DESTACO property. Do not disclose to or duplicate for others except as authorized by DESTACO.

COMPONENT		Pneumatic Toggle Clamps	
DIMENSIONS : [IN] MM	807-U	REV	
TOLERANCES : ±[0.020] 0.51		SHEET	1 of 1
807-SERIES			