


NOTES :

1. MAX. HOLDING CAPACITY : [4040 lbs] 18000 N
2. EXERTING FORCE : [1124 lbs] 5000 N
3. WEIGHT : [3.30 lbs.] 1,5 kg
4. WHEN L = [9.84] 250, RAPID STROKES = 100
5. WHEN L = [13.78] 350, RAPID STROKES = 200
6. WHEN L = [17.76] 451, RAPID STROKES = 300
7. DIMENSIONS AND TOLERANCES SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

b1	b2	l1	l2	l3	l4	l5	l6
[1.97] 50	[2.68] 68	[3.23] 80	[1.97] 50	[0.71] 18	[1.38] 35	[0.79] 20	[0.08] 2
l7	l8	d1H7	d2H8	d3	d4	d5	R
[1.97] 50	[0.47] 12	[0.39] 10	[0.63] 16	[1.58] 40	[0.33] 8,3	[0.33] 8,5	[6.50] 165



COMPONENT

Variable Stroke Straight Line Action Clamps

DIMENSIONS : [IN] MM

F-160

REV

01/24/19

TOLERANCES : ±[0.020] 0.51

F-160-SERIES

SHEET

1 of 1



15 Corporate Drive,
Auburn Hills, MI 48326, USA
Phone: 888-337-8226, Fax: 800-682-9689
www.destaco.com

This Drawing is the Property of DESTACO.
It contains confidential, proprietary
information that is DESTACO property. Do
not disclose to or duplicate for others
except as authorized by DESTACO.