


12/07/2020



cesehsa.com.mx



DESTACO Custom Catalog

12/07/2020

This catalog is a custom document and the products included is based on your unique selection from portions of complete catalogs that already exist. Please refer to our full catalogs for more information on products not included in this customized document.

Table of Contents

Robot Adaptors

EE-ADP-1


Table of Contents (continued)

ROBOT ADAPTER MOUNTS

Table of Contents



Adaptor Mount Assemblies and Components 3-28



Mid-Mount Flanges 29




Tooling Mounting Blocks 38


ROBOT ADAPTER MOUNTS

Robot Automation Adaptors | Selection Guide - Manual Tool Changers RDN-25 Series


STYLE 1 (ACMX58)




STYLE 2 (FA500)




STYLE 3 (KW150)




STYLE 4 (FA900)




STYLE 5 (KA760)




STYLE 6 (MMNY300)




STYLE 7 (FA430I)




STYLE 8 (FA420)



STYLE 9 (ABB44)




STYLE 10 (KWZ165)



STYLE 11 (KWUT120)




STYLE 12 (FA710)



STYLE 14 (MMK100)



STYLE 15 (KA660)



STYLE 16 (FA2000)




STYLE 18 (MMHP165-125)




STYLE 19 (MMHP165-92)




STYLE 21 (EOAMC30)



STYLE 22 (FA900-SSM)



STYLE 23 (MD350)



STYLE 24 (SA000)




ROBOT ADAPTER MOUNTS

Robot Automation Adaptors | Selection Guide - Manual Tool Changers RDN-25 Series


250 SERIES ROBOT ADAPTOR SELECTION GUIDE										
ADAPTOR MOUNTS		MOUNTING PATTERN			DOWELS			PILOT		DWG PAGE
STYLE (MODEL)	TYPE AVAIL.	BOLT CIRCLE	BOLT SIZE	BOLTS QTY	BOLT CIRCLE	DWL SIZE	DWL QTY	DIAMETER (Ø)	DEPTH	
STYLE 1 (ACMX58)	DM/90	Ø90mm [Ø3.54"]	M8	8	Ø80mm [Ø3.15"]	10mm	4	N/A	N/A	4
STYLE 2 (FA500)	DM/90	Ø90mm [Ø3.54"]	M10	8	Ø90mm [Ø3.54"]	10mm	4	Ø59.5mm [Ø2.34"]	4.8 [.19]	5
STYLE 3 (KW150)	DM/90	Ø92mm [Ø3.62"]	M10	6	Ø92mm [Ø3.62"]	9mm	2	Ø54mm [Ø2.13"]	6.4 [.25]	6
STYLE 4 (FA900)	DM/90	Ø125mm [Ø4.92"]	M10	6	Ø125mm [Ø4.92"]	10mm	2	Ø79.5mm [Ø3.13"]	6.4 [.25]	7
STYLE 5 (KA760)	DM/90	Ø160mm [Ø6.30"]	M10	6	Ø160mm [Ø6.30"]	10mm	2	Ø99.9mm [Ø3.94"]	6.4 [.25]	8
STYLE 6 (MMNY300)	DM	Ø200mm [Ø7.87"]	M12	6	Ø200mm [Ø7.87"]	12mm	1	N/A	N/A	9
STYLE 7 (FA430I)	DM/90	Ø125mm [Ø4.92"]	M10	6	Ø125mm [Ø4.92"]	10mm	2	Ø79.5mm [Ø3.13"]	6.4 [.25]	10
STYLE 8 (FA420)	DM	Ø92mm [Ø3.62"]	M10	8	Ø92mm [Ø3.62"]	10mm	4	Ø79.5mm [Ø3.13"]	4.8 [.19]	11
STYLE 9 (ABB44)	DM/90	Ø100mm [Ø3.94"]	M10	6	Ø100mm [Ø3.94"]	8mm	2	Ø61.9mm [Ø2.44"]	6.4 [.25]	12
STYLE 10 (KWZ165)	DM/90	Ø125mm [Ø4.92"]	M10	10	Ø125mm [Ø4.92"]	10mm	2	Ø79.5mm [Ø3.13"]	6.4 [.25]	13
STYLE 11 (KWUT120)	90	Ø120mm [Ø4.72"]	M8	8	Ø120mm [Ø4.92"]	8mm	2	N/A	N/A	14
STYLE 12 (FA710)	DM	Ø100mm [Ø3.94"]	M8	6	Ø100mm [Ø3.94"]	8mm	2	N/A	N/A	15
STYLE 14 (MMK100)	90	Ø125mm [Ø4.92"]	M10	6	Ø125mm [Ø4.92"]	10mm	2	Ø61mm [Ø2.40"]	6.4 [.25]	16
STYLE 15 (KA660)	DM/90	Ø160mm [Ø6.30"]	M12	6	Ø160mm [Ø6.30"]	12mm	1	Ø99mm [Ø3.90"]	6.4 [.25]	17
STYLE 16 (FA2000)	DM	Ø125mm [Ø4.92"]	M10	10	Ø125mm [Ø4.92"]	10mm	2	Ø79.5mm [Ø3.13"]	6.4 [.25]	18
STYLE 18 (MMHP165)	DM/90	Ø125mm [Ø4.92"]	M10	6	Ø125mm [Ø4.92"]	10mm	2	Ø62.5mm [Ø2.46"]	6.4 [.25]	19
STYLE 19 (MMHP165)	90	Ø92mm [Ø3.62"]	M10	6	Ø125mm [Ø4.92"]	9mm	2	Ø62.5mm [Ø2.46"]	6.4 [.25]	20
STYLE 21 (EOAMC30)	DM	Ø127mm [Ø5.00"]	3/8-16	6	Ø108mm [Ø4.25"]	.25"(in)	2	N/A	N/A	21
STYLE 22 (FA900-SSM)	DM	Ø125mm [Ø4.92"]	M10	6	Ø125mm [Ø4.92"]	10mm	2	Ø79.5mm [Ø3.13"]	4.8 [.19]	21
STYLE 23 (MD350)	DM/90	Ø187.3mm [Ø7.38"]	3/8-16	4	Ø187.3mm [Ø7.38"]	3/8	2	N/A	N/A	22
STYLE 24 (SA000)	DM	Ø69.5mm [Ø2.74"]	M10	4	N/A	N/A	N/A	N/A	N/A	23

Style 01 - **ACMX58** 90° Robot Adaptor (Ø90mm Bolt Circle/Ø80mm Dowel Circle)

Models Supported:
ACMA X58



Style 01 - **ACMX58** 90° Robot Adaptor (Ø90mm Bolt Circle/Ø80mm Dowel Circle)




FA500

Robot Automation Adaptors | Dimensions


Style 02 - FA500 Direct Mount Adaptor (Ø90mm Bolt Circle)

Models Supported:

FANUC M-400
FANUC M-500
FANUC S-420 (WITH
FANUC FLANGE)




Style 02 - FA500 90° Robot Adaptor (Ø90mm Bolt Circle)



Style 03 - KW150 90° Robot Adaptor (Ø92mm Bolt Circle)


Models Supported:

KAWASAKI UX100
KAWASAKI UX120
KAWASAKI UX150



MODEL NUMBER	PORTING	# OF PORTS	WEIGHT
CPI-KW150-DM-RD25-A3	3/8 NPT	3 (2/1)	1.45 kg [3.19 lb]
CPI-KW150-DM-RD25-A6	1/8 NPT	6 (3/3)	1.49 kg [3.28 lb]

Style 03 - KW150 90° Robot Adaptor (Ø92mm Bolt Circle)



MODEL NUMBER	WEIGHT
CPI-KW150-90-RD25-A36	3.63 kg [8.01 lb]


FA900

Robot Automation Adaptors | Dimensions


Style 04 - FA900 Direct Mount Adaptor (Ø125mm Bolt Circle)

Models Supported:

ABB IRB 60(00)
ABB IRB 64(00)
FANUC R-2000I(6-BOLT)
FANUC M-410
FANUC S-900
MOTOMAN SP100X




Style 04 - FA900 90° Robot Adaptor (Ø125mm Bolt Circle)




Style 05 - **KA760** Direct Mount Adaptor (Ø160mm Bolt Circle)

Models Supported:

KUKA IW 125
KUKA PL 150
KUKA IW 150
KUKA PL 125
KUKA KR 125
KUKA ZH 125
KUKA IR 760
KUKA ZH 150



Style 05 - **KA760** 90° Robot Adaptor (Ø160mm Bolt Circle)




MMNY300

Robot Automation Adaptors | Dimensions

Style 06 - MMNY300 Direct Mount Adaptor (Ø200mm Bolt Circle)


Models Supported:
MOTOMAN SP100X
KUKA KR 350




MODEL NUMBER	PORTING	# OF PORTS	WEIGHT
CPI-MMNY300-DM-RD25-A3	3/8 NPT	3 (2/1)	3.56 kg [7.84 lb]
CPI-MMNY300-DM-RD25-A6	1/8 NPT	6 (3/3)	3.61 kg [7.95 lb]

Style 07 - FA430i Direct Mount Adaptor (Ø125mm Bolt Circle)

Models Supported:
FANUC S430i



Style 07 - FA430i 90° Robot Adaptor (Ø125mm Bolt Circle)







FA420

Robot Automation Adaptors | Dimensions

Style 08 - FA420 Direct Mount Adaptor (Ø92mm Bolt Circle)

Models Supported:
FANUC S420 (WITH
SPECIAL FLANGE)




MODEL NUMBER	PORTING	# OF PORTS	WEIGHT
CPI-FA420-DM-RD25-A3-SPC	3/8 NPT	3 (2/1)	1.48 kg [3.27 lb]
CPI-FA420-DM-RD25-A6-SPC	1/8 NPT	6 (3/3)	1.52 kg [3.35 lb]


Style 09 - ABB44 Direct Mount Adaptor (Ø100mm Bolt Circle)

Models Supported:

ABB IRB 4400/S
ABB IRB 4400/60
ABB IRB 4400/45
ABB IRB 4400/L30



Style 09 - ABB44 90° Robot Adaptor (Ø100mm Bolt Circle)




MODEL NUMBER	WEIGHT
CPI-ABB44-90-RD25-A36	3.24 kg [7.15 lb]

KWZ165


Robot Automation Adaptors | Dimensions

Style 10 - KWZ165 Direct Mount Adaptor (Ø125mm Bolt Circle)


Models Supported:
KAWASAKI Z165



Style 10 - KWZ165 90° Robot Adaptor (Ø125mm Bolt Circle)



Style 11 - KWUT120 90° Adaptor (Ø120mm Bolt Circle)



Models Supported:
KAWASAKI UT120


MODEL NUMBER	WEIGHT
CPI-KWUT120-90-RD25-A36	3.58 kg [7.90 lb]

FA710

Robot Automation Adaptors | Dimensions


Style 12 - FA710 Direct Mount Adaptor (Ø100mm Bolt Circle)

Models Supported:
FANUC M710



MODEL NUMBER	PORTING	# OF PORTS	WEIGHT
CPI-FA710-DM-RD25-A6	1/8 NPT	6 (3/3)	1.43 kg [3.15 lb]

Style 14 - **MMK100** 90° Adaptor (Ø125mm Bolt Circle)



Models Supported:
COMAU CMH3.2
MOTOMAN K100
MOTOMAN UP130




MODEL NUMBER	WEIGHT
CPI-MMK100-90-RD25-A36	4.03 kg [8.88 lb]

KA660


Robot Automation Adaptors | Dimensions

Style 15 - KA660 Direct Mount Adaptor (Ø160mm Bolt Circle)

Models Supported:
KUKA 660




Style 15 - KA660 90° Robot Adaptor (Ø160mm Bolt Circle)




Style 16 - FA2000 Direct Mount Adaptor (Ø125mm Bolt Circle)

Models Supported:
FANUC R2000I



Style 16 - FA2000 90° Robot Adaptor (Ø125mm Bolt Circle)




MMHP165


Robot Automation Adaptors | Dimensions



Style 15 - **KA660** Direct Mount Adaptor (Ø160mm Bolt Circle)

Models Supported:
MOTOMAN ES165N
MOTOMAN HP165



Style 15 - **KA660** 90° Robot Adaptor (Ø125mm Bolt Circle)






MODEL NUMBER	WEIGHT
CPI-MMHP165-92-90-RD25-A36	4.03 kg [8.89 lb]


EOAMC30, FA900-SSM

Robot Automation Adaptors | Dimensions


Style 21 - **EOAMC30** Direct Mount Adaptor (Ø127mm Bolt Circle/Ø108mm Dowel Circle)




Style 22 - **FA900-SSM** Direct Mount Adaptor (Ø125mm Bolt Circle)



Style 23 - MD350 Direct Mount Adaptor - Ø187.3mm Bolt Circle




Style 23 - MD350 90° Robot Adaptor




SA000

Robot Automation Adaptors | Dimensions

Style 24 - SA000 Direct Mount Adaptor - Ø69.5mm Bolt Circle




CM975XL Direct Mount Adaptor - Ø76mm Bolt Circle



MODEL NUMBER	PORTING	# OF PORTS	WEIGHT
CPI-CM675XL-DM-RD25-A3	3/8 NPT	3 (2/1)	1.47 kg [3.24 lb]

CHM32 Direct Mount Adaptor - Ø125mm Bolt Circle




MODEL NUMBER	PORTING	# OF PORTS	WEIGHT
CPI-CHM32-DM-RD25-A3	3/8 NPT	3 (2/1)	2.38 kg [5.25 lb]
CPI-CHM32-DM-RD25-A6	1/8 NPT	6 (3/3)	2.42 kg [5.34 lb]


FA710, FA710IC

Robot Automation Adaptors | Dimensions

FA710IC 90° Robot Adaptor - Ø100mm Bolt Circle





FA710IC 90° Robot Adaptor - Ø100mm Bolt Circle



TDA-150F, TDA-250F



Robot Automation Adaptors | Dimensions

TDA-150F Direct Mount Adaptor Plate - Ø85mm Bolt Circle



MODEL NUMBER	WEIGHT
CPI-TDA-150F-312F	.62 kg [1.36 lb]

TDA-250F Direct Mount Adaptor Plate - Ø125mm Bolt Circle




MODEL NUMBER	WEIGHT
CPI-TDA-250F-312F	.63 kg [1.38 lb]


FA900, KW150

Robot Automation Adaptors | Dimensions





FA900 Direct Mount Adaptor Plate - Ø125mm Bolt Circle



KW150 Direct Mount Adaptor Plate - Ø92mm Bolt Circle



90° Degree Robot Adaptor to 40mm Disk




MODEL NUMBER	WEIGHT
CPI-KWFS45N-90-TTN40-A3	4.24 kg [9.34 lb]

CL-LAN


Robot Automation Adaptors | Dimensions

Ø125mm Bolt Circle




MODEL NUMBER	WEIGHT
CPI-CL-LAN-EOL	5.25 kg [11.58 lb]

90° Medium Duty - Ø125mm Bolt Circle




MODEL NUMBER	WEIGHT
CPI-ATI-151-90-WT	3.64 kg [8.03 lb]



MODEL NUMBER	WEIGHT
CPI-ATI-90	3.55 kg [7.82 lb]

90° Light Duty - Ø125mm Bolt Circle



MODEL NUMBER

CPI-ATI-90-SP


WEIGHT

3.64 kg [8.03 lb]

ATI-201-60

Robot Automation Adaptors | Dimensions

Ø125mm Bolt Circle




MODEL NUMBER	WEIGHT
CPI-ATI-201-60	2.29 kg [5.06 lb]

ATI-201-XXX-90

Robot Automation Adaptors | Dimensions

Ø125mm Bolt Circle Dowels





MODEL NUMBER	(Ø) "D"	(Ø) ACTUAL	WEIGHT
CPI-ATI-201-60-90	60mm	60.45 \pm .08 [2.380 \pm .003]	1.27 kg [2.80 lb]
CPI-ATI-201-250-90	2.50"(in)	63.96 \pm .08 [2.518 \pm .003]	1.27 kg [2.80 lb]

ATI-150-90-3HD






Robot Automation Adaptors | Dimensions

Ø125mm Bolt Circle



MODEL NUMBER	WEIGHT
CPI-ATI-201-90-3HD	2.50 kg [5.52 lb]

90° World Tool Assembly - Ø125mm Bolt Circle





MODEL NUMBER


CPI-ATI-201-250-90-10S

WEIGHT

2.17 kg [4.77 lb]




MODEL NUMBER	(Ø) "D"	(Ø) ACTUAL	WEIGHT
CPI-NAV-25-CM	25mm	25.25 \pm .08 [0.994 \pm .003]	[2.60 lb]
CPI-NAV-100-CM	1.00"(in)	25.65 \pm .08 [1.010 \pm .003]	1.18 kg



DRILL AND TAP FOR
M10-1.50 .75 DEEP (2)

MODEL NUMBER	(Ø) "D"	(Ø) ACTUAL	WEIGHT
CPI-NAV-25-BL	25mm	25.25 \pm .08 [0.994 \pm .003]	[.89 lb]
CPI-NAV-100-BL	1.00"(in)	25.65 \pm .08 [1.010 \pm .003]	.40 kg



GLOBAL LOCATIONS

NORTH AMERICA

Corporate Headquarters

Auburn Hills, Michigan
Toll Free: 1.888.DESTACO
Marketing: marketing@destaco.com

Global Technology Center

Auburn Hills, Michigan
Tel: 1.248.836.6700
Customer Service: customerservice@destaco.com

Mt. Juliet, Tennessee
Tel: 1.888.DESTACO
Customer Service: customerservice@destaco.com

Wheeling, Illinois
Tel: 1.800.645.5207
Customer Service: camco@destaco.com

Red Wing, Minnesota (Central Research Laboratories)
Tel: 651.385.2142
Customer Service: sales@centres.com

ASIA

Thailand
Tel: +66-2-326-0812
Customer Service: info@destaco.com

China
Tel: +86-21-6081-2888
Customer Service: china@destaco.com

India
Tel: +91-80-41123421-426
Customer Service: india@destaco.com

EUROPE

Germany
Tel: +49-6171-705-0
Customer Service: europe@destaco.com

France
Tel: +33-4-73545001
Customer Service: france@destaco.com

Great Britain
Tel: +44-1902-797980
Customer Service: uk@destaco.com

Spain
Tel: +34-936361680
Customer Service: spain@destaco.com

Netherlands
Tel: +31-297285332
Customer Service: benelux@destaco.com