



Socio de Servicios Autorizado de Alfa Laval en México cesehsa.com.mx

Alfa Laval TL6

Gasketed plate-and-frame heat exchanger for a wide range of applications

Alfa Laval Industrial line is a wide product range that is used in virtually all types of industry.

The relatively tall plate makes this model suitable for duties with long temperature programs and when high heat recovery is appreciated. A large range of plate and gasket types is available.

Applications

- Biotech and Pharmaceutical
- Chemicals
- · Energy and Utilities
- Food and Beverages
- Home and Personal care
- HVAC and Refrigeration
- · Machinery and Manufacturing
- Marine and Transportation
- Mining, Minerals and Pigments
- Pulp and Paper
- Semiconductor and Electronics
- Stee
- Water and Waste treatment

Benefits

- High energy efficiency low operating cost
- Flexible configuration heat transfer area can be modified
- Easy to install compact design
- High serviceability easy to open for inspection and cleaning and easy to clean by CIP
- Access to Alfa Laval's global service network

Features

Every detail is carefully designed to ensure optimal performance, maximum uptime and easy maintenance. Selection of available features:

- Corner guided alignment system
- Chocolate pattern distribution area
- Clip-on gasket
- Leak chamber
- Fixed bolt head
- Key hole bolt opening
- Lifting lug
- Lining
- Lock washer
- Tightening bolt cover



Extending performance

with Alfa Laval 360° Service Portfolio

Our extensive services ensure op performance from your Alfa Laval equipment throughout its life cycle. The availability of parts and our team's commitment and expertise bring you peace of mind.

Start-up

- Installation
- Installation Supervision
- Commissioning

Maintenance

- Cleaning Services
- Reconditioning
- Repair
- Service Tools
- Spare Parts

Support


- Exclusive Stock
- Technical Documentation
- Telephone Support
- Training
- Troubleshooting

Improvements

- Equipment Upgrades
- Redesign
- Replacement and Retrofit

Monitoring

- Condition Audit
- Performance Audit



Type	Н	W	h
TL6-FM	1264 (49.8")	320 (12.6")	137 (5.4")
TL6-FG	1264 (49.8")	320 (12.6")	137 (5.4")
TL6-FG, ASME	1299 (51.1")	320 (12.6")	142 (5.6")
TL6-FD	1264 (49.8")	330 (13.0")	137 (5.4")
TL6-FD, ASME	1308 (51.5")	330 (13.0")	142 (5.6")

The number of tightening bolts may vary depending on pressure rating.

Technical data

Plates

Name	Туре	Free channel, mm (inches)
TL6-B	Single plate	1.8 (0.071)

Materials	
Heat transfer plates	304/304L, 316/316L, 254
	C-276
-	Ti
Field gaskets	NBR, EPDM, FKM
Flange connections	Carbon steel
	Metal lined: stainless steel, titanium
	Rubber lined: NBR, EPDM
Pipe connections	Stainless steel
Frame and pressure plate	Carbon steel, epoxy painted

Other materials may be available on request.

All option combinations may not be configurable.

Operational data

Frame, PV-code	Max. design pressure (barg/psig)	Max. design temperature (°C/°F)
FM, pvcALS	10.0/145	180/356
FM, PED	10.0/145	180/356
FG, pvcALS	16.0/232	180/356
FG, ASME	10.3/150	250/482
FG, PED	16.0/232	180/356
FD, pvcALS	25.0/363	180/356
FD, ASME	20.7/300	250/482
FD, PED	25.0/362	180/356

Extended pressure and temperature rating may be available on request.

Pipe	connections
------	-------------

i ipo dominodiono	
Threaded port	ISO 228 - G 2
External parallel threaded	ISO 228 - G 2 B

Other connection types may be available on request.

Flange	connections
--------	-------------

FM, pvcALS	EN 1092-1 DN50/DN65 PN16
	ASME B16.5 Class 150 NPS 2
	JIS B2220 10K 50A/65A
FM, PED	EN 1092-1 DN50/DN65 PN16
	ASME B16.5 Class 150 NPS 2
FG, pvcALS	EN 1092-1 DN50/DN65 PN16
	ASME B16.5 Class 150 NPS 2
	JIS B2220 10K 50A/65A
	JIS B2220 16K 50A/65A
FG, ASME	ASME B16.5 Class150 NPS 2
FG, PED	EN 1092-1 DN50/DN65 PN16
	ASME B16.5 Class 150 NPS 2
FD, pvcALS	EN 1092-1 DN50/DN65 PN40
	ASME B16.5 Class 300 NPS 2
	JIS B2220 20K 50A/65A
FD, ASME	ASME B16.5 Class 300 NPS 2
FD, PED	EN 1092-1 DN50/DN65 PN40
	ASME B16.5 Class 300 NPS 2

Standard EN1092-1 corresponds to GOST 12815-80 and GB/T 9115.

CHE00083EN 2016-04

Alfa Laval reserves the right to change specifications without prior notification.



