84N5 Series

Universal Sheet Metal Press Shop Gripper

DESTACO's 84N5 sheet metal gripper is the universal solution for press shop gripping applications. The 84N5 gripper accelerates your press tending productivity with a lighter, faster and highly flexible gripper that can accommodate most press shop needs. The 84N5 features easy in-field jaw reconfiguration, adjustable opening angle, multipoint sensing and minimal field maintenance.


Developed for high-speed automation now you can increase your productivity using lighter tooling weighing as little as 0.68kg with an actuation speed of 70ms and a grip force up to 1200N. The small footprint of this gripper will fit into existing applications for easy system upgrades.

Designed and tested for long life, this patented gripper requires minimal maintenance. A variety of sheet metal thickness tips, field changeable jaw kits, multiple blank and double blank sensing solutions provide extreme versatility. With the wide offering of mounting options, the 84N5 is a universal press shop gripper solution.

Product Highlights/Options

- Full range adjustable jaw opening
- Interchangeable jaws
- Fast on-site configuration changeover
- Optional multipoint sensing •
- Easy field maintenance

Features, Markets and Applications



^{*}When compared with our closest competition







Cesehsa

México info@cesehsa.com.mx cesehsa.com.mx



ACCELERATE









SSEMBLY

ACCELERATE® PRESS SHOP GRIPPER

84N5 Series Sheet Metal Grippers

The 84N5 Universal Sheet Metal Gripper is available in three jaw types. The modular design allows the jaws to be exchanged in the field quickly and easily with the use of a single allen wrench.



Multipoint Side Mount Sensing: for open/closed, single and double blank sensing



Optional Angle Adjustment Kit: for multiple jaw openings in one gripper





Optional In-Jaw Sensor for part present sensing

Parallel Swivel Mount For 30mm Bodybuilder (Shown)

US Patent #10549431

Additional mounts available.

84N5-X-075-FA Fixed Lower Jaw



84N5-X-075-DA Double Open Jaw



84N5-X-075-PA 90° Jaw Configuration



Interchangeable Jaw Tips: Single & double cone or serrated style tips can be used in different configurations for different contact points and part thicknesses





ACCELERATE® PRESS SHOP GRIPPER

84N Series Jaw Options | Flexible and Adjustable

84N5-X-ADJ-XX

Jaw Opening

Set to 15°

(Open)

Field Adjustable Jaw Opening

The 84N5 sheet metal gripper with angle adjustment kit option installed allows jaw opening angle to be adjusted quickly in the field from 15° up to maximum 75° simply with the turn of the stopper.



Convenient Angle Marking For easy identification of jaw opening angle



Interchangeable Jaw Tips: To allow the handling of multiple part thickness



Part Thickness Range Option 1 0.4 - 1.0mm



Part Thickness Range Option 2 1.0 - 1.6mm



Part Thickness Range Option 3 1.6 - 2.2mm



Part Thickness Range Option 4 2.2 - 2.8mm



2.2 - 2.8mm Part Thickness

Range Option 5 2.8 - 3.4mm



Adjustable Sheet Stop The included sheet stop can also be adjusted in the field to change the jaw depth









Optional Mounts (Sold Separately) Offered in applecore, ball, and swivel

Offered in applecore, ball, and swive options for use in most applications



Side Mount Apple Core 19mm 20mm





Parallel Swivel Mount 1.00in/25mm 1.25in/30mm BB



Rear Ball Mount 32mm Ball



Rear Flange Mount 35.1 x 57mm Mounting pattern



Rear Swivel Mount 25mm





DESTACO's 84N5 Series is latest addition to the family of Accelerate® Press Shop Sheet Metal Grippers





DESTACO 84N Series Accelerate® Press Shop Sheet Metal Grippers are up to:

60% lighter* (0.27-0.68kg)

40% smaller* foot print

62% faster* actuation (33-70ms)

100% DESTACO innovation

*When compared with our closest competition

Specification Unit 84N1/84N2 84N5 Grip Force at 5 bar Ν Up to 1000 Up to 1200 Weight (FA jaws - no tips) 0.27 0.68 Kg Size L x W x H (Open) 110 x 43 x 64 149 x 46 x 95 mm 70 Actuation Time 33 ms 3 4 Minimum Operating Pressure bar 30°, 45°, 60°, 75° 75°, ADJ (15°-75°) **Opening Angles** 32 Piston Ø 25 mm Air Consumption/Cycle .015 .036 L

Dimensions and technical information are subject to change without notice.

GERMANY +49-6171-705-0 europe@destaco.com

FRANCE Tel: +33-4-7354-5001 france@destaco.com UNITED KINGDOM +44-1902-797980 uk@destaco.com

SPAIN +34-936361680 spain@destaco.com NETHERLANDS +31-297285332 benelux@destaco.com

CHINA +86-21-6081-2888 china@destaco.com THAILAND +66-2-326-0812 asia@destaco.com

INDIA +91-80-41123421-426 india@destaco.com USA +1-888-DESTACO +1-248-836-6700 northamerica@destaco.com