

84N Series

Sheet Metal Press Room Gripper Products

DESTACO Introduces the newest addition to its line of stamping press sheet metal gripping solutions.

The Accelerate® sheet metal press room gripper is half the weight and more compact, with faster actuation — when compared to our closest competition⁽¹⁾ — without sacrificing grip force which measures up to 1000 N at 5 bar.

The lighter, smaller and faster 84N series gripper accelerates stamping press operations by helping customers produce more stamped parts per hour with higher efficiency while reducing moment forces and overall system wear and tear.



Product Highlights/Options

- Standard, chisel and 90° jaw options
- 30° , 45° , 60° and 75° jaw opening available
- Flexible mounting options
- Part present sensing
- One-step tip adjustment tool







Features, Markets and Applications



- 12% smaller footprint (*)
- Zero protrusion fixed jaw
- No protrusion of top jaw mechanism below body



- 60% lighter, weighing only 0.27kg (vs 0.56kg) (*)
- Body constructed of lightweight aluminum



- 60% faster actuation time at 33ms (vs 50ms) (*)
- Compact and powerful, with a grip force up to 1000N at 5 bar
- Integrated clamp-loss protection















ACCELERATE® PRESS ROOM GRIPPER

84N1 Series Sheet Metal Gripper with Adjustable Tips



84N2 Series Sheet Metal Gripper with Fixed Tips







Part Thickness Range Option 1 0.4 - 1.0mm



Part Thickness Range Option 2 1.0 - 1.6mm



Part Thickness Range Option 3 1.6 - 2.2mm



Part Thickness Range Option 4 2.2 - 2.8mm



Part Thickness Range Option 5 2.8 - 3.4mm



ACCELERATE® PRESS ROOM GRIPPER

84N Series Mounting and Sensor Options







Sensor Kit



84N2 with Rear Flange Mount and Double Blank Detector Sensor Kit

84N1 with 32mm Side Ball Mount and Infrared PNP Sensor Kit



84N Series Sheet Metal Gripper used with Accelerate Lightweight Tooling.







84N2 Standard Fixed Lower Jaw Double Tip Serrated Insert Parallel Swivel Mount Infrared PNP Sensor

The Accelerate® Press Room Sheet Metal Gripper is:

60% lighter* (0.27kg vs 0.56kg)

12% smaller* foot print

parts of any size and shape

thoughout the stamping process.

60% faster* actuation (33ms vs 50ms)

100% DESTACO innovation

*When compared with our closest Competition

Specification	Unit	
Grip Force at 5 bar	Ν	Up to 1000
Weight (FC00 version)	Kg	.27
Size L x W x H (closed)	mm	110 x 43 x 43
Size L x W x H (open)	mm	110 x 43 x 64
Actuation Time	ms	33
Life	cycles	5 million
Minimum Operating Pressure	bar	1
Opening Angles		30°, 45°, 60°, 75°
Piston Ø	mm	25
Air Consumption/Cycle	L	.015

Dimensions and technical information are subject to change without notice.